



Description

Gas detector are part of the new gas detector range for industrial and tertiary application. The detector has a head with a sensitive semiconductor element to measure explosive gas concentration on LEL (Low Explosive Limit) scale. The detector is pre-set on Prewarning level of 15% and Warning at 30% of LEL. For toxicity NH₃ 100 ppm prewarning and 200 ppm warning cod 07 and 1000 ppm prewarning and 2000 ppm warning cod 08. A handheld programmer and a PC software are optionally available; with them it is possible to conduct a field test of the detector and to change the configuration: detection threshold, alarm filters, addressing, full scale, etc. Head replacement can be done only by manufacturer. The detector is supplied with explosion-proof metal case unit with ATEX II 2G Ex-d IIC T6 certification for the location of the electronic communication and of the sensitive element, that is placed into the lower part and protected by a sintered filter in resined steel enclosure.


Models

MOON serie gas detectors are provided with two electronic boards; one for calibration algorithm control and sensitive element compensation (1), a second one to manage communication towards controlling system (2).

The detector comes with one of the following communication cards:

- 42** Analogue output model of 4-20 mA, both active and passive, positive or negative. Typical connection for application with PLC. Possibility of calibrating the full scale signal values.
- RL 3** Relay output module for Prewarning and Warning. Dry contact outputs can be set as NA or NC, normally used for the connection in burglary systems or directly used for electrical boards.
- LV** Communication module for analogue boards with Teledata protocol. The module can transmit prewarning, warning and fault information using a single Loop address (depending on the central system). Up to 240 detectors for Loop.

G7-BASE-2 CARD



HELPCARD

Rilevamenti

E55500XX	Metano
E55502XX	Vapori di benzina
E55504XX	H ₂
E55505XX	GPL
E55506XX	Propano
E55507XX	NH ₃ 0-500 PPM
E55508XX	NH ₃ 0-2000 PPM



Technical data

Supply voltage	12/24 Vdc
Sensitive element	Semiconductor
Power consumption in stand-by	70 mA max
Power consumption in alarm	100 mA max
Operating temperature	0°C / +40 °C
Relative humidity	90%
Enclosure	ATEX ADPE
Weight	1000 g
Dimension (HxWxD)	165x90x80
Ø Screw	1" GAS
ATEX II 2G Ex-d IIC T6 Certified	